

S.E.R.E.M.E.

31 rue Gutenberg
ZI de La Marinière
91070 BONDOUFLE – France
Tel : 33 (1) 60 86 42 36 – Fax : 33 (1) 60 86 52 55
sereme@sereme.com

DATA SHEET (Rev 10/2024)

Manufacturer : SEREME
Société d'Etudes et Réalisations de Moyens d'Essais

Model : **Acoustic Modulator SERMOD MF45**



TECHNICAL DATA :

Acoustic performances : Confidential data – subject to signature of NDA

Operating noise range : 20 Hz – 8000 Hz

Controllability range : 20 Hz – 1000 Hz

Operating temperature range : 15° C – 30 ° C

Gas supply : Air or Nitrogen

Maximum inlet pressure : 2,5 bar

Maximum flow : $\leq 1,8$ kg / s

Coil resistance : $\sim 2,20$ Ohm

Maximum intensity : ≤ 12 Amp RMS

Monitoring measurement on 5 channels : option

Visual control : with glass zoom 5

WORKING CONDITIONS :

Nominal inlet pressure : 2,2 bar

Nominal flow : 1,60 kg / s

Nominal Intensity : 7 Amp RMS

All values for information only

This document is SEREME's sole property and cannot be used or reproduced without SEREME's authorization.